

KB-GS20-S

Item	Specification
Spec for Country	Singapore
Feature	20 Selection, 2 Room 1 Row Can Rack + 3 Row PET Rack (2 Row P Rack + 1 Row Wide P Rack)
Dimensions (mm)	Width 999 × Depth 712 (Front 45 without Billvalidator + Body 667) × Height 1830
Back Clearance	50mm
Sales Variation	20 Selection, 20 Buttons
Coin Mechanism	Factory default not equipped
Bill Validator	Factory default not equipped
Power Specification	Single phase 220 V ~ 240V 50Hz

Selection Button No. and temperature patterns (Factory Default)	<Selection Button No>	<Hot/Cold Display Patterns>																			
	<table border="1"> <tr><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td></tr> <tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td></tr> </table>	11	12	13	14	15	16	17	18	19	20	1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20												
1	2	3	4	5	6	7	8	9	10												

Column Structure	<table border="1"> <tr><td>1</td><td>6</td><td>11</td><td>16</td></tr> <tr><td>2</td><td>7</td><td>12</td><td>17</td></tr> <tr><td>3</td><td>8</td><td>13</td><td>18</td></tr> <tr><td>4</td><td>9</td><td>14</td><td>19</td></tr> <tr><td>5</td><td>10</td><td>15</td><td>20</td></tr> </table>	1	6	11	16	2	7	12	17	3	8	13	18	4	9	14	19	5	10	15	20
1	6	11	16																		
2	7	12	17																		
3	8	13	18																		
4	9	14	19																		
5	10	15	20																		
Column Configuration																					

Rack Type	N P P Y ※ N : W=146.5mm P : W=238mm Y : W=275mm
-----------	---

Hot/Cold Patterns	<table border="1"> <tr><td>COLD</td><td>COLD</td></tr> <tr><td>HOT</td><td>COLD</td></tr> </table>	COLD	COLD	HOT	COLD
COLD	COLD				
HOT	COLD				



Capacity by Column
 - : Sales outside the scope (Sales are not allowed)

Type of product	Diameter mm	Volume m L	Column number																				Total
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
Slim Can	53	190	25	23	20	18	15	25	23	20	18	15	25	23	20	18	15	-	-	-	-	303	
		250	25	23	20	18	15	25	23	20	18	15	25	23	20	18	15	-	-	-	-	303	
Wide Can	60	280	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	-	-	-	-	237	
		350	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	316
		500	-	-	-	-	-	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	237
P E T Bottle (Circle shaped)	69	280	20	18	16	14	12	20	18	16	14	12	20	18	16	14	12	-	-	-	-	240	
		500	-	-	-	-	-	18	17	15	13	11	18	17	15	13	11	18	17	15	13	11	222
		600	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	17	16	14	12	10

NOTES:
 1. Above "Capacity by Column" table is based on Japanese standard packaging. Capacity may vary depending on the stockpile condition inside the rack.
 2. Depending on the packaging size and hardness, some merchandise may not be suitable for sale.

Other Specification			
Item	Specification	Item	Specification
Mechanical		Electrical	
1.Handle	Kubota standard	1. Lighting specification	L E D line type
2.Lock	Kubota standard		
3.Upper Hinge	Internal hinge		
4.Middle Hinge	N/A	2. Remote Keyboard	Kubota standard
5.Billvalidator cover	N/A		Counter built-in, 4-line display LCD
6.Unadjusted mechanism	2010 K mech PET, KLP-C(Plate equipped)		
7.Rack Type	K Rack		
8.Deliveryport port	Kubota standard		
9.POS panel	N/A		
Heating/Cooling			
1.Compressor	reciprocating		
2.Refrigerant	R134a		
3.Heating system	Heater (left room)		