METEC SEMARANG

For Earth, For Life
Kubota

KUBOTA Vending Machine

KB-GS24-S
Kubota Can & Bottle
Vending Machine 24 Selection

KB-GS20-S
Kubota Can & Bottle
Vending Machine 20 Selection

KB-GS30-S
Kubota Can & Bottle
Vending Machine 30 Selection

Simple Operation
(All Type)

Hot & Cold Setting
(KB-GS-Series)

Multi Drop Bus Interface (MDB)
(All Type)

Indoor & Outdoor Placement
(KB-GS-Series)

Energy Saving Technology
(All Type)

TPK Vending Corporation Co., Ltd.

KB-GS24-S
SPECIFICATION

Feature	:	24 Selections 2 Rooms, 4 Row PET Rack (3 Row P Rack + 1 Row Y Rack)
Dimensions (mm)	:	Width 1160× Depth 805 (Front 56 without Bill - validator + Body 749) × Height 1846
Selection Button No.	:	24
Coin Mechanism	:	Factory default not equipped
Bill Validator	:	Factory default not equipped
Capacity	:	428pcs (Sleek Can 325ml)
Power Specification	:	Single phase 220V - 240V, 50 Hz
Temperature Range	:	Chilled 4 ± 4°C, Heated 55 ± 4.5°C

Lightning	:	Line-type LED
Rate Input Power	:	665W
Power Consumption	:	2,4 kwh/day
Vending System	:	Rack Vending Mechanical
Refrigerant	:	R134a/220g
Empty Weight	:	285kg

Selection Button No

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24

Structure Column



Capacity By Column

Type of product	Diameter mm	Volume m L	Column number 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	Total
Slim Can	53	190	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	-	-	-	-	-	-	369
		250	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	-	-	-	-	-	-	369
Sleek Can	58	325	24	20	19	17	15	12	24	20	19	17	15	12	24	20	19	17	15	12	24	20	19	17	15	12	428
Wide Can	66	280	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	-	-	-	-	-	-	285
		350	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	380
		500	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	380
PET Bottle (Circle	69	280	21	19	17	15	13	11	21	19	17	15	13	11	21	19	17	15	13	11	-	-	-	-	-	-	288
		500	20	17	16	14	12	10	20	17	16	14	12	10	20	17	16	14	12	10	20	17	16	14	12	10	356
	69.1～	600	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	18	16	15	13	11	9	82

Note:
1. Above "Capacity by Column" table is based on Japanese standard packaging. Capacity may vary depending on the stockpile condition inside the rack.
2. Depending on the packaging size and hardness, some merchandise may not be suitable for sale.

KB-GS20-S
SPECIFICATION

Feature	:	20 Selections 2 Rooms, 3 Row PET Rack (Including 1 Row for 600ml PET Bottles)
Dimensions (mm)	:	Width 999 × Required Depth 712 (Front 45 + Body 667) × Height 1846
Selection Button No.	:	20
Coin Mechanism	:	Factory default not equipped
Bill Validator	:	Factory default not equipped
Capacity	:	316pcs (Can 350ml)
Power Specification	:	Single phase 220V - 240V, 50 Hz
Temperature Range	:	Chilled 4 ± 4°C, Heated 55 ± 4.5°C

Lightning	:	Line-type LED
Rate Input Power	:	665W
Power Consumption	:	2,9 kwh/day
Vending System	:	Rack Vending Mechanical
Refrigerant	:	R134a/220g
Empty Weight	:	235kg

Selection Button No

11	12	13	14	15	16	17	18	19	20
1	2	3	4	5	6	7	8	9	10

Structure Column



Capacity By Column

Type of product	Diameter mm	Volume ml	Column number 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	Total
Slim Can	53	190	25	23	20	18	15	25	23	20	18	15	25	23	20	18	15	—	—	—	—	—	303
		250	25	23	20	18	15	25	23	20	18	15	25	23	20	18	15	—	—	—	—	—	303
Wide Can	66	280	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	—	—	—	—	—	237
		350	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	316
		500	—	—	—	—	—	19	18	16	14	12	19	18	16	14	12	19	18	16	14	12	237
PET Bottle	69	280	20	18	16	14	12	20	18	16	14	12	20	18	16	14	12	—	—	—	—	—	240
		500	—	—	—	—	—	18	17	15	13	11	18	17	15	13	11	18	17	15	13	11	222
	69.1～73	600	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	17	16	14	12	10	69

Note:
1. Above "Capacity by Column" table is based on Japanese standard packaging. Capacity may vary depending on the stockpile condition inside the rack.
2. Depending on the packaging size and hardness, some merchandise may not be suitable for sale.

KB-GS30-S
SPECIFICATION

Feature	:	30 Selections 2 Rooms, 3 Row PET Rack (Including 1 Row for 600ml PET Bottles)
Dimensions (mm)	:	Width 1160 × Required Depth 794 (Front 45 + Body 749) × Height 1846
Selection Button No.	:	30
Coin Mechanism	:	Factory default not equipped
Bill Validator	:	Factory default not equipped
Capacity	:	475pcs (Can 350ml)
Power Specification	:	Single phase 220V - 240V, 50 Hz
Temperature Range	:	Chilled 4 ± 4°C, Heated 55 ± 4.5°C

Lightning	:	Line-type LED
Rate Input Power	:	665W
Power Consumption	:	2,7 kwh/day
Vending System	:	Rack Vending Mechanical
Refrigerant	:	R134a/220g
Empty Weight	:	290kg

Selection Button No

21	22	23	24	25	26	27	28	29	30
11	12	13	14	15	16	17	18	19	20
1	2	3	4	5	6	7	8	9	10

Structure Column



Capacity By Column

Type of product	Diameter mm	Volume ml	Column number 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	Total
Slim Can	53	190	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	—	—	—	—	—	—	492
		250	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	27	24	22	19	17	14	—	—	—	—	—	—	492
Wide Can	66	280	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	—	—	—	—	—	—	380
		350	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	475
		500	—	—	—	—	—	—	—	—	—	—	—	—	21	18	17	15	13	11	21	18	17	15	13	11	21	18	17	15	13	11	285
PET Bottle	69	280	21	19	17	15	13	11	21	19	17	15	13	11	21	19	17	15	13	11	21	19	17	15	13	11	—	—	—	—	—	—	384
		500	—	—	—	—	—	—	—	—	—	—	—	—	20	17	16	14	12	10	20	17	16	14	12	10	20	17	16	14	12	10	267
	69.1～73	600	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	18	16	15	13	11	9	82

Note:
1. Above "Capacity by Column" table is based on Japanese standard packaging. Capacity may vary depending on the stockpile condition inside the rack.
2. Depending on the packaging size and hardness, some merchandise may not be suitable for sale.

Jpn Vending Corporation Co., Ltd.